



LED FLOOD LIGHTS



Anale LED Flood Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Grey
Driver Type	External

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 90% RH
Vibrations	1G

HOW TO ORDER

HUB - ANALE - 50W - GR

Input Power	1	Colour Temperature (CCT)	2
30W :	30W	2732K :	2700K - 3200K
50W :	50W	4050K :	4000K - 5000K
100W :	100W	6050K :	6000K - 6500K
150W :	150W	RD :	Red
200W :	200W	RD :	Red
		GR :	Green
		GR :	Green
		BL :	Blue

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - ANALE - 50W - GR



Lenico LED Flood Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Black
Driver Type	External

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 2KV
External Surge Protection @ 10KV	Yes
Short Circuit Protection	Yes
Impact Protection	IK07
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 90% RH
Vibrations	1G

HOW TO ORDER

HUB - LENICO -

400W

2732K

Input Power	1	Colour Temperature (CCT)	2
400W : 400W		2732K : 2700K - 3200K	
800W : 800W		4050K : 4000K - 5000K	
		6050K : 6000K - 6500K	

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - LENICO - 400W - 2732K



Setti LED Flood Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	120 Degrees

Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 90% RH
Vibrations	1G

HOW TO ORDER

HUB - SETTI - 100W - 6050K

Input Power	1	Colour Temperature (CCT)	2
10W :	10W	2732K :	2700K - 3200K
20W :	20W	4050K :	4000K - 5000K
30W :	30W	6050K :	6000K - 6500K
50W :	50W		
70W :	70W		
100W :	100W		
150W :	150W		
200W :	200W		
250W :	250W		

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - SETTI - 100W - 6050K