



## Andis LED Flood Lights

### General Specifications

Mounting Type	Surface
Beam Angle	60 Degrees
Lighting Source Type	SMD LED

### Fixture Specifications

Housing Material	Die Cast Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Black
Driver Type	External

### Performance Specifications

Colour rendering index (CRI)	70+
Efficacy (Lm / W)	110+

### Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 20%
Input Frequency	50 to 60 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 90%

### Safety Features

Ingress Protection	IP66
--------------------	------

### Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

## HOW TO ORDER

**HUB - ANDIS - 300W - 2732K**

Input Power	1	Colour Temperature (CCT)	2
<b>50W :</b> 50W		<b>2732K :</b> 2700K - 3200K	
<b>100W :</b> 100W		<b>4050K :</b> 4000K - 5000K	
<b>200W :</b> 200W		<b>6050K :</b> 6000K - 6500K	
<b>300W :</b> 300W			

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - ANDIS - 300W - 2732K**