



## Assels Decorative Lamps

### General Specifications

|               |           |
|---------------|-----------|
| Mounting Type | Suspended |
|---------------|-----------|

### Fixture Specifications

|                  |               |
|------------------|---------------|
| Housing Material | Aluminium     |
| Surface Finish   | Powder Coated |

### Electrical Specifications

|                     |              |
|---------------------|--------------|
| Input Voltage (VAC) | 90 - 300 VAC |
| Input Frequency     | 50 to 60 Hz  |

### Safety Features

|                    |      |
|--------------------|------|
| Ingress Protection | IP20 |
|--------------------|------|

### Packaging Specifications

|                       |                     |
|-----------------------|---------------------|
| Luminaries Per Box    | 1                   |
| Dimension (L X W X H) | 210 X 210mm X 360mm |

### Environmental Specification

|                     |           |
|---------------------|-----------|
| Working Temperature | 0 to 40 C |
| Vibrations          | 1G        |

### Mechanical Specifications

|          |               |
|----------|---------------|
| Height   | 13.8" (350mm) |
| Diameter | 7.9" (200mm)  |

## HOW TO ORDER

HUB - ASSELS - WH

|                |       |
|----------------|-------|
| Housing Colour | 1     |
| WH :           | White |
| BL :           | Black |

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - ASSELS - WH**