



Getto LED Uplighters

General Specifications

Mounting Type	Recessed
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

Fixture Specifications

Housing Material	Stainless Steel
Diffuser Material	Polycarbonate

Performance Specifications

Rated LED Burning Hours	50,000 Hrs
Start up time	Instant

Electrical Specifications

Input Frequency	NA
-----------------	----

Safety Features

Ingress Protection	IP68
Short Circuit Protection	NA
Impact Protection	IK07
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 100%
Vibrations	1G

HOW TO ORDER

HUB - GETTO - -

Input Power	<input type="text" value="1"/>	Colour Temperature (CCT)	<input type="text" value="2"/>
1W : 1W		2732K : 2700K - 3200K	
3W : 3W		4050K : 4000K - 5000K	
7W : 7W		6050K : 6000K - 6500K	
12W : 12W			
20W : 20W			
30W : 30W			
40W : 40W			

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - GETTO - 7W - 6050K