



HSSA LED Street Lights

General Specifications

Mounting Type	Pole
Limited Warranty	2 Years
Beam Angle	120 Degrees
Lighting Source Type	SMD LED

Fixture Specifications

Diffuser Material	Polycarbonate
Housing Colour	Grey
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Safety Features

Ingress Protection	IP65
--------------------	------

Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

Solar System Specifications

Solar Panel	5V Poly
Charging Time	6 - 8 Hrs
System Type	Integrated
Battery Type	LiFePo4

HOW TO ORDER

HUB - HSSA - 15W - 4050K

Input Power	1	Colour Temperature (CCT)	2
5W : 5W		2732K : 2700K - 3200K	
10W : 10W		4050K : 4000K - 5000K	
15W : 15W		6050K : 6000K - 6500K	
20W : 20W			
25W : 25W			

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - HSSA - 15W - 4050K