# HUBLIT



### **HOW TO ORDER**



#### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value.Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

#### Example : HUB - PURCH - 2W/F - WH - 6050K

## Purch LED Linear Cove Lights

#### **General Specifications**

deneral opeenicatione	
Limited Warranty	2 Years
Lighting Source Type	SMD LED
Fixture Specifications	
Housing Material	Extruded Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Anodised
Driver Type	External
Performance Specifications	
Colour rendering index (CRI)	80+
Start up time	Instant
Efficacy (Lm / W)	100+
Electrical Specifications	
Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Power Factor	0.95 +
Driver Efficiency	Upto 80%
Safety Features	
Ingress Protection	IP44
Surge Protection	Upto 2KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes
Environmental Specification	
Working Temperature	0 to 40 C
Vibrations	1G
Mechanical Specifications	
Luminaire Dimension (L X W X H)	50mm X 51mm

HUBLIT