



Setti LED Flood Lights

General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	120 Degrees

Fixture Specifications

Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	70+
Rated LED Burning Hours	50,000 Hrs
Colour Temperature (CCT)	6000K - 6500K
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	90 - 300 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP65
Surge Protection	Upto 4KV
Short Circuit Protection	Yes
Open Circuit Protection	Yes
Over Voltage Protection	Yes

Environmental Specification

Working Temperature	0 to 55 C
Working Humidity	upto 90% RH
Vibrations	1G

HOW TO ORDER

HUB - SETTI

50W

4050K

Input Power	1	Colour Temperature (CCT)	2
10W : 10W		2732K : 2700K - 3200K	
20W : 20W		4050K : 4000K - 5000K	
30W : 30W		6050K : 6000K - 6500K	
50W : 50W			
70W : 70W			
100W : 100W			
150W : 150W			
200W : 200W			
250W : 250W			

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - SETTI - 50W - 4050K