



## Therns LED Bendable Linear Lights

### General Specifications

Mounting Type	Surface
Limited Warranty	2 Years
Beam Angle	60 Degrees
Lighting Source Type	SMD LED

### Fixture Specifications

Housing Shape	Sqaure
Surface Finish	Glossy
Housing Colour	White
Driver Type	External

### Performance Specifications

Colour rendering index (CRI)	80+
Start up time	Instant
Efficacy (Lm / W)	90+

### Electrical Specifications

Input Voltage (VAC)	120 - 270 VAC
Total Harmonic Distorsion	Upto 20%
Input Frequency	50 to 60 Hz
Power Factor	0.90 +
Driver Efficiency	Upto 80%

### Safety Features

Ingress Protection	IP65
Surge Protection	Upto 2KV
Open Circuit Protection	Yes

### Environmental Specification

Working Temperature	0 to 40 C
Vibrations	1G

## HOW TO ORDER

HUB - THERNS

1W/FT

4050K

Colour Temperature (CCT)

2

**2732K :** 2700K - 3200K

**4050K :** 4000K - 5000K

**6050K :** 6000K - 6500K

**RD :** Red

**RD :** Red

**GR :** Green

**GR :** Green

**BL :** Blue

### How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

**Example : HUB - THERNS - 1W/FT - 4050K**