



Tropa LED Spike Lights

General Specifications

Limited Warranty	2 Years
Beam Angle	30 Degrees

Fixture Specifications

Housing Material	Extruded Aluminium
Diffuser Material	Polycarbonate
Surface Finish	Powder Coated
Housing Colour	Black
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	80+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP66
Short Circuit Protection	Yes
Impact Protection	IK07
Open Circuit Protection	Yes

Packaging Specifications

Luminaries Per Box	1
--------------------	---

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	upto 90%
Vibrations	1G

Smart Features

Lux Sensing	Optional
Motion Sensing	Optional

HOW TO ORDER

HUB - TROPA - 10W - 2732K

Input Power	1	Colour Temperature (CCT)	2
5W : 5W		BL : Blue	
10W : 10W		2732K : 2700K - 3200K	
12W : 12W		4050K : 4000K - 5000K	
15W : 15W		6050K : 6000K - 6500K	
		RD : Red	
		RD : Red	
		GR : Green	
		GR : Green	

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - TROPA - 10W - 2732K