



Venty LED Filament Bulbs

General Specifications

Mounting Type	Retrofit
Limited Warranty	2 Years
Beam Angle	270 Degrees

Fixture Specifications

Housing Material	Polycarbonate
Diffuser Material	Polycarbonate
Housing Colour	White
Driver Type	Integrated

Performance Specifications

Colour rendering index (CRI)	80+
Rated LED Burning Hours	50,000 Hrs
Start up time	Instant
Efficacy (Lm / W)	100+

Electrical Specifications

Input Voltage (VAC)	150 - 270 VAC
Total Harmonic Distorsion	Upto 10%
Input Frequency	50 Hz
Power Factor	0.95 +
Driver Efficiency	Upto 80%

Safety Features

Ingress Protection	IP20
Short Circuit Protection	Yes
Open Circuit Protection	Yes

Packaging Specifications

Luminaries Per Box	1
--------------------	---

Environmental Specification

Working Temperature	0 to 40 C
Working Humidity	Upto 80%
Vibrations	1G

HOW TO ORDER

HUB - VENTY - 12W - 2732K

Input Power	1	Colour Temperature (CCT)	2
3W : 3W		2732K : 2700K - 3200K	
5W : 5W		4050K : 4000K - 5000K	
7W : 7W		6050K : 6000K - 6500K	
12W : 12W			

How to order example

To order a Hublit products, you can choose an Input Power from the values above from the minimum value to the maximum value, in this case we use smallest value. Similarly you can choose from the Colour Temperature (CCT) options from 2700K to 6500K and so on to generate the model number; Please find the example of a filled model number for this product.

Example : HUB - VENTY - 12W - 2732K